


REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	ZQJ 11/18/2014	~	ZQJ 11/18/2014
B	ADD P/N CODE	CJJ 11/18/2014	~	

- NOTES:
- MATERIAL&FINISHES
 - INSULATOR:THERMOPLASTIC(UL 94V-0).
 - CONTACT MATERIAL: COPPER ALLOY.
 - SPECIFICATION
 - CURRENT RATING:1.5 Amp.
 - INSULATION RESISTANCE:1000MΩ Min.
 - DIELECTRIC WITHSTANDING:600VAC.
 - CONTACT RESISTANCE:20mΩ Max.
 - OPERATING TEMPERATURE:-40°C TO +105°C.

TABLE A

TYPE	Dimension			Pin Length
	A	B	C	
1	4.00	2.80	9.30	10.70 14.70
2	6.00	2.80	11.30	12.70 16.70
3	2.42	5.00	12.70	16.10 20.10
4	3.70	3.00	9.00	10.30 14.30
5	3.20	3.00	9.20	10.50 14.50
6	8.00	2.80	13.30	14.70 18.70
7	3.50	3.00	9.25	10.50 14.50
8	4.00	4.00	9.30	11.70 15.70
9				
10				

A&B: CUSTOMER LENGTH AVAILABLE
 N: NUMBER OF CONTACTS/2



RECOMMEND PCB LAYOUT
 (TOLERANCE=±0.05)

GENERAL TOLERANCE	ANGLE TOLERANCE	PROJECTION	⊕	TITLE	2.0MM PIN HEADER DUAL ROW		
X. ±0.60	X. ±5°	UNITS	mm	R/A Type			
.X ±0.38	.X ±3°	SHEET SIZE	A4	SERIES	LL1011-4		
.XX ±0.25	.XX ±2°	慈溪蓝翎电子有限公司 CIXI LANLING ELECTRONICS CO., LTD. 慈翎电子					
DRAWING TYPE	CUSTOMER						
SCALE	1:1						SHEET 1 OF 1
DRAWING NO.							