



REV	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	ZGJ 11/18/2014		
B	ADD PIN CODE	CJJ 11/18/2014		

- NOTES:
- ELECTRICAL:
 - Current rating: 3Amps/contact max.
 - Contact resistance: $\leq 20m\Omega$ /contact
 - Insulation resistance: $\geq 1000M\Omega$ at $V=100V$.
 - Operating voltage: 60V AC/DC.

2. PRODUCT NUMBER CODE:
LL1019-5 - X X X X

- CLIP PLATING
 - 6: Full Tin
 - 8: Full gold flash
 - C: Full gold 3u"
 - A: Full gold 10u"
- PIN PLATING
 - 6: Full Tin
 - 8: Full gold flash
 - C: Full gold 3u"
 - A: Full gold 10u"
- NO. OF CONTACTS
 - 1*1 to 1*40
 - 2*2 to 2*40

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE	
X	± 0.60	X	$\pm 5'$	UNITS	mm	IC SOCKET PITCH 2.54mm	
X	± 0.38	X	$\pm 3'$	SHEET SIZE	A4	PIN LENGTH 4.20mm	
XX	± 0.25	XX	$\pm 2'$			LL1019-5	
DRAWING TYPE		CUSTOMER		SERIES			
SCALE		1:1		SHEET			
DRAWING NO.				10F1			

慈溪蓝翎电子有限公司
CIXI LANLING ELECTRONICS CO., LTD.