



REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	ZQJ 11/18/2014	~	ZQJ 11/18/2014
B		CJJ 11/18/2014	~	

- NOTES:
- ELECTRICAL CHARACTERISTICS:
 - CONTACT RESISTANCE: 20mΩ Max. INITIAL.
 - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC(rms) FOR 1 MINUTE.
 - INSULATION RESISTANCE: 1000MΩ Min.
 - ENVIRONMENT CHARACTERISTICS:
 - TEMPERATURE: -40°C~+105°C.
 - PRODUCT NUMBER CODE:
 LL1020-4 X X X
 CONTACT TYPE
 1: TYPE 1 3: TYPE 3
 2: TYPE 2 4: TYPE 4
 CONTACT PLATING
 F1: Full GOLD FLASH
 No.OF CONTACTS
 1*1 - 1*40
 2*1 - 2*40

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION	⊕	TITLE	DIP STRIPADAPTER PITCH 2.54mm
X.	±0.60	X.	±5°	UNITS	mm		PIN LENGTH=7.64mm/8.51mm
.X	±0.38	.X	±3°	SHEET SIZE	A4	SERIES	LL1020-4
.XX	±0.25	.XX	±2°	慈溪蓝翎电子有限公司 CIXI LANLING ELECTRONICS CO., LTD. 蓝翎电子 Tel: 86-574-63519036 Fax: 86-574-63517070			
DRAWING TYPE		CUSTOMER					
SCALE	1:1	SHEET	10F1				
DRAWING NO.							