

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	ZQJ 11/18/2015	~	ZQJ 11/18/2015
B	ADD P/N CODE	CJJ 11/18/2015	~	CJJ 11/18/2015


材质 Material

SLOT-2.54-180度

绝缘体 Insulator	Class Filled PBT UL94V-0 Black
接触件 Contacts	Brass/Phosphor Bronze
电镀层 Plating	Contact Gold and Dip Tin over Nickel

电气性能 Electrical Characteristics

接触电阻 Contact Resistance	30mΩ max at DC100mA
绝缘电阻 Insulator Resistance	1000MΩ min at 500V DC
耐压 Withstanding Voltage	1000V AC/rms 50Hz for 1 min
工作电流 Current Rating	3 AMP
使用温度范围 Operating Temp	-55°C~+105°C



Dimension

Position	A	B	C	D	E
40	83.80	76.80	66.80	60.33	71.20
44	90.15	83.15	73.15	66.68	77.55
56	109.20	102.20	92.20	85.73	96.60
60	115.55	108.55	98.55	92.08	102.95
72	134.60	127.60	117.60	111.13	122.00
80	147.30	140.30	130.30	123.83	134.70
86	156.83	149.83	139.83	133.35	144.23
100	179.05	172.05	162.05	155.58	166.45

GENERAL TOLERANCE	ANGLE TOLERANCE
X, ±0.60	X, ±5°
X, ±0.38	X, ±3°
.XX, ±0.25	.XX, ±2°

PROJECTION UNITS	TITLE
mm	3.96mm Edge Cord Connector Slot
SHEET SIZE	SERIES
A4	LL1038-3

2	CONTACT
1	HOUSING
ITEM	PART NAME

DRAWING TYPE	CUSTOMER
SCALE	1:1
DRAWING NO.	SHEET
	1 OF 1


**慈溪蓝翎电子有限公司**  
 CIXI LANLING ELECTRONICS CO., LTD.  
 蓝翎电子